


WINDFLEX® 600 PU AL



- 1 Copper color steel spiral
- 2 Wall in transparent polyurethane



FLEXIBLE DUCTING IN POLYURETHANE ETHER WITH WALL REINFORCED WITH A GALVANIZED STEEL WIRE HELIX. SPRING QUALITY.

Potential equalisation, earthed at the ends of the steel spiral. PU rated non flammable UL94 V2. Halogen free.

APPLICATIONS

Suction of: Sawdust and chips, air and fumes, oil vapour extraction

SECTORS OF ACTIVITY

Wood industry


Windflex® 600 PU AL suitable for dried foodstuffs only.

MARKING

↓ WINDFLEX® 600 PU (EU) N°10/2011 ↓ Ø inn

[Batch number]
Made in France

mm	+/- mm	mm	g/m	mbar	mm	Transparent		
						5 m	10 m	mini of order (m)
40	0/+2,0	0,6	250	250	25		174720	10
51	0/+2,0	0,6	290	250	32		174721	10
60	0/+2,0	0,6	340	200	37		174719*	30
70	0/+3,0	0,6	430	140	43		174731	10
80	0/+3,0	0,6	500	100	49		174760*	30
90	0/+3,0	0,6	550	100	56		174761*	30
102	0/+4,0	0,6	560	90	63		174722	10
120	0/+4,0	0,6	710	80	74		174723	10
127	0/+4,0	0,6	750	80	78		174730	10
140	0/+4,0	0,6	830	80	86		174762*	20
152	0/+5,0	0,6	900	60	94		174724	10
160	0/+5,0	0,6	940	60	99		174725	10
180	0/+5,0	0,6	1060	50	111		174726	10
203	0/+5,0	0,6	1250	50	125		174727	10
254	0/+5,0	0,6	1560	50	157		174728	10
305	0/+6,0	0,6	1880	30	188		174729	10
350	0/+6,0	0,6	2620	20	216		174763*	10
400	0/+6,0	0,6	3000	20	247	174764*		5
500	0/+6,0	0,6	3750	10	309	174765*		5
600	0/+6,0	0,6	5000	10	370	174614*		5



ADVANTAGES

WINDFLEX® 600 PU AL ducting is extremely flexible and due to the 100% ether-based polyurethane wall offers very good mechanical resistance. Extremely good abrasion resistance, flexibility and elasticity. Remarkable for its wide temperature range of use.

CONNECTORS

Connectors with wire collars. Small diameters can be screwed into themselves. We recommend checking before assembly that the fittings cannot harm the inner wall.

CHEMICAL RESISTANCE

See table pages 114 to 117 column C.

*on request: delivery time 4 weeks

WE HAVE THE POSSIBILITY TO MANUFACTURE OTHER LENGTHS AND DIAMETERS ON REQUEST. CONSULT US.

delivery in coils except compressed articles